

List of Figures

Figure No.	Title	Page No.
1.1	Investments in advanced ceramics by developed countries during last decade	1
1.2	Schematics of (a) electron Polarization (b) ionic Polarization (c) orientational Polarization (d) space charge Polarization	8
1.3	The influence of the Polarization (a) real part of relative permittivity and (b) imaginary part of relative permittivity with frequency	9
1.4	Argand diagram for dielectric material with only one relaxation time based on Debye equation	10
1.5	The Schematic of ϵ'_r , ϵ''_r and $\tan\delta$ as function of ω based on Debye equation	11
1.6	The Cole-Cole plot for dielectric material with a set of relaxation time based on Cole-Cole equation	12
1.7	The classified categories of Dielectric Materials	14
1.8	The Cell-Structure of a natural composite, a tree	16
1.9	Spider Silk	17
1.10	Composite materials with different types of reinforcements	19
1.11	Service temperature ranges of some important polymers, metals and ceramics	22
1.12	The structure of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ (Cu - Blue, Oxygen-Red, Ca- Yellow)	27
1.13	Temperature-dependence of ϵ (a), $\tan\delta$ and (b) angular relaxation rate at (c) 10^2 , 10^3 , 10^4 , 10^5 and 10^6 Hz	28

1.14	Polarized Raman Spectra of CCTO at room temperature	29
1.15	Complex impedance plot Z'' Vs. Z' at (a) 300K and (b) 104, 115 and 130K, for CCTO ceramics. The inset in (a) shows expanded views of the high frequency data close to the origin. Filled symbols indicate selected frequencies in Hz	31
1.16	SEM images of ceramic microstructure for CCTO ceramics sintered at 1100 ⁰ C for (a) 3h and (b) 24h	32
1.17	Schematic of twin boundary in $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$	33
1.18	(a) Temperature – dependent dielectric constants and (b) Conductivities of Single-Crystalline $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ with sputter gold (Solid Lines) and Silver-Paint contacts (Symbols) at various frequencies. The dashed and dashed-dotted Lines in (b) show an estimate of the intrinsic bulk dc conductivity and contribution of the insulating layer.	34
1.19	(a) Frequency-dependent dielectric constants, (b) Loss, and (c) Conductivities of Single Crystalline $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ with silver-paint contacts at various temperatures.	35
1.20	Schematic diagram of a section through an internal barrier layer capacitor (IBLC).	36
2.1	Temperature dependence of the Spontaneous polarization.	42
2.2	The Hysteresis Loop	43
2.3	ABO_3 Perovskite Structure	45

2.4	Ten Connectivity Patterns in Diphasic Composites	64
4.1	The mixed oxide route of CCTO Ceramic preparation	72
4.2	Flow chart of the composite preparation	75
4.3	Schematic diagram of an X-ray diffractometer; T is the X-ray source, S the specimen, C the detector and O the axis around which the specimen and detector rotate.	76
4.4	Schematic representation of various processes.	80
4.5	Frequency dependence of ϵ' and ϵ'' and an Argand diagram Debye Model	81
4.6	Frequency dependence of Z' and Z''	84
4.7	The Schematic diagram of the set up used for measuring the dielectric constant.	85
4.8	A set up to study conductivity of the samples	86
5.1	Densities of CCTO : PET Composites	88
5.2	Densities of CCTO : PVC Composites	88
5.3	X-Ray diffractogram of CCTO Ceramic	90
5.4	X-Ray diffractogram of 90% CCTO : 10% PVC Ceramic polymer composite.	91
5.5	X-Ray diffractogram of 80% CCTO : 20% PVC Ceramic Polymer composite.	92
5.6	X-Ray diffractogram of 70% CCTO : 30% PVC Ceramic Polymer composite.	93
5.7	X-Ray diffractogram of 60% CCTO : 40% PVC Ceramic Polymer composite.	94
5.8	X-Ray diffractogram of 50% CCTO : 50% PVC	

	Ceramic Polymer composite.	95
5.9	X-Ray diffractogram of 40% CCTO : 60% PVC Ceramic Polymer composite.	96
5.10	X-Ray diffractogram of 30% CCTO : 70% PVC Ceramic Polymer composite.	97
5.11	X-Ray diffractogram of 90% CCTO : 10% PET Ceramic Polymer composite.	98
5.12	X-Ray diffractogram of 80% CCTO : 20% PET Ceramic Polymer composite.	99
5.13	X-Ray diffractogram of 70% CCTO : 30% PET Ceramic Polymer composite.	100
5.14	X-Ray diffractogram of 60% CCTO : 40% PET Ceramic Polymer composite.	101
5.15	X-Ray diffractogram of 50% CCTO : 50% PET Ceramic Polymer composite.	102
5.16	X-Ray diffractogram of 40% CCTO : 60% PET Ceramic Polymer composite	103
5.17	X-Ray diffractogram of 30% CCTO : 70% PET Ceramic Polymer composite	104
5.18	SEM Photograph of Pure PVC	105
5.19	SEM Photograph of 30% CCTO 70% PVC composite	106
5.20	SEM Photograph of 40% CCTO 60% PVC composite	106
5.21	SEM Photograph of 50% CCTO 50% PVC composite	107
5.22	SEM Photograph of 60% CCTO 40% PVC composite	107
5.23	SEM Photograph of 70% CCTO 30% PVC composite	108
5.24	SEM Photograph of 80% CCTO 20% PVC composite	108
5.25	SEM Photograph of 90% CCTO 10% PVC composite	109

5.26	SEM Photograph of Pure PET Sample	109
5.27	SEM Photograph of 30% CCTO 70% PET composite	110
5.28	SEM Photograph of 40% CCTO 60% PET composite	110
5.29	SEM Photograph of 50% CCTO 50% PET composite	111
5.30	SEM Photograph of 60% CCTO 40% PET composite	111
5.31	SEM Photograph of 70% CCTO 30% PET composite	112
5.32	SEM Photograph of 80% CCTO 20% PET composite	112
5.33	SEM Photograph of 90% CCTO 10% PET composite	113
5.34	SEM Photograph of CCTO Ceramic	113
5.35	Dielectric Constant of CCTO Ceramic	115
5.36	Dielectric Constant of 90% CCTO: 10% PVC Ceramic Polymer Composite	116
5.37	Dielectric Constant of 90% CCTO : 10% PET Ceramic Polymer Composite	117
5.38	Dielectric Constant of 80% CCTO : 20% PVC Ceramic Polymer Composite	118
5.39	Dielectric Constant of 80% CCTO : 20% PET Ceramic Polymer Composite	119
5.40	Dielectric Constant of 70% CCTO : 30% PVC Ceramic Polymer Composite	120
5.41	Dielectric Constant of 70% CCTO : 30% PET Ceramic Polymer Composite	121
5.42	Dielectric Constant of 60% CCTO : 40% PVC Ceramic Polymer Composite	122
5.43	Dielectric Constant of 60% CCTO : 40% PET Ceramic Polymer Composite	123

5.44	Dielectric Constant of 50% CCTO : 50% PVC Ceramic Polymer Composite	124
5.45	Dielectric Constant of 50% CCTO : 50% PET Ceramic Polymer Composite	125
5.46	Dielectric Constant of 40% CCTO : 60% PVC Ceramic Polymer Composite	126
5.47	Dielectric Constant of 40% CCTO : 60% PET Ceramic Polymer Composite	127
5.48	Dielectric Constant of 30% CCTO : 70% PVC Ceramic polymer Composite	128
5.49	Dielectric Constant of 30% CCTO : 70% PET Ceramic polymer Composite	129
5.50	Dielectric loss of CCTO Ceramic with temperature at various frequencies	131
5.51	Dielectric loss of 90% CCTO : 10% PVC Ceramic polymer Composite	132
5.52	Dielectric loss of 90% CCTO : 10% PET Ceramic polymer Composite	133
5.53	Dielectric loss of 80% CCTO : 20% PVC Ceramic polymer Composite	134
5.54	Dielectric loss of 80% CCTO : 20% PET Ceramic polymer Composite	135
5.55	Dielectric loss of 70% CCTO : 30% PVC Ceramic polymer Composite	136
5.56	Dielectric loss of 70% CCTO : 30% PET Ceramic polymer Composite	137

5.57	Dielectric loss of 60% CCTO : 40% PVC Ceramic polymer Composite	138
5.58	Dielectric loss of 60% CCTO : 40% PET Ceramic polymer Composite	139
5.59	Dielectric loss of 50% CCTO : 50% PVC Ceramic polymer Composite	140
5.60	Dielectric loss of 50% CCTO : 50% PET Ceramic polymer Composite	141
5.61	Dielectric loss of 40% CCTO : 60% PVC Ceramic polymer Composite	142
5.62	Dielectric loss of 40% CCTO : 60% PET Ceramic polymer Composite	143
5.63	Dielectric loss of 30% CCTO : 70% PVC Ceramic polymer Composite	144
5.64	Dielectric loss of 30% CCTO : 70% PET Ceramic polymer Composite	145
5.65	Plot of Log Conductivity Vs. Inverse Temperature of CCTO Ceramic	147
5.66	Plot of Log Conductivity Vs. Inverse Temperature of CCTO 90% : PVC 10% Ceramic Polymer Composite	148
5.67	Plot of Log Conductivity Vs. Inverse Temperature of CCTO 90% : PET 10% Ceramic Polymer Composite	149
5.68	Plot of Log Conductivity Vs. Inverse Temperature of CCTO 80% : PVC 20% Ceramic Polymer	

	Composite	150
5.69	Plot of Log Conductivity Vs. Inverse Temperature of CCTO 80% : PET 20% Ceramic Polymer Composite	151
5.70	Plot of Log Conductivity Vs. Inverse Temperature of CCTO 70% : PVC 30% Ceramic Polymer Composite	152
5.71	Plot of Log Conductivity Vs. Inverse Temperature of CCTO 70% : PET 30% Ceramic Polymer Composite	153
5.72	Plot of Log Conductivity Vs. Inverse Temperature of CCTO 60% : PVC 40% Ceramic Polymer Composite	154
5.73	Plot of Log Conductivity Vs. Inverse Temperature of CCTO 60% : PET 40% Ceramic Polymer Composite	155
5.74	Plot of Log Conductivity Vs. Inverse Temperature of CCTO 50% : PVC 50% Ceramic Polymer Composite	156
5.75	Plot of Log Conductivity Vs. Inverse Temperature of CCTO 50% : PET 50% Ceramic Polymer Composite	157
5.76	Plot of Log Conductivity Vs. Inverse Temperature of CCTO 40% : PVC 60% Ceramic Polymer Composite	158

5.77	Plot of Log Conductivity Vs. Inverse Temperature of CCTO 40% : PET 60% Ceramic Polymer Composite	159
5.78	Plot of Log Conductivity Vs. Inverse Temperature of CCTO 30% : PVC 70% Ceramic Polymer Composite	160
5.79	Plot of Log Conductivity Vs. Inverse Temperature of CCTO 30% : PET 70% Ceramic Polymer Composite	161
5.80	Activation Energies of CCTO : PVC Ceramic Polymer Composites as a function of % of CCTO	163
5.81	Activation Energies of CCTO : PET Ceramic Polymer Composites as a function of % of CCTO	164

LIST OF TABLES

Table No.	Title	Page No.
1.1	Categories of Ceramics	4
1.2	Dielectric and Cell Edge for $ACu_3Ti_4O_{12}$ (at $25^{\circ}C$)	26
5.1	Densities of PET: CCTO and PVC : CCTO Composites	87
5.2	Activation energies of the various composites studied	162