

List of Figures

Fig No	Name of the Figure	Page No
1.1	Some parts manufactured by sheet metal forming operation	3
1.2	Deep drawing of a cylindrical cup (a) before drawing and (b) after drawing	4
1.3	Stretch forming of a sheet	5
1.4	Sheet bending using U-die and V-die	5
1.5	Conventional Flow forming principle	7
1.6	Stresses and deformation in a section of a cup during deep drawing	8
1.7	Punch force vs punch stroke diagram for deep drawing process	10
1.8	Fracture in deep drawing	11
1.9	Wrinkling in deep drawing	12
1.10	Earing in deep drawing	13
2.1	Forward and Backward flow forming	19
2.2	Manufacture of Internal Geared wheel	21
2.3	Drive shaft flange	22

3.1	Cause and Effect diagram	40
4.1	Schematic of Experimental setup for flow forming	43
4.2	Tooling for 10% reduction in the thickness of 2 mm sheet	47
4.3	Tooling for 25% reduction in the thickness of 2 mm sheet	47
4.4	Tooling for 40% reduction in the thickness of 2 mm sheet.	48
4.5	Complete experimental test rig	50
4.6	Punch Die and Blank Holder Setup	51
4.7	Induction furnace used for heating the blank.	54
4.8	Induction coil connected to the Inconel die for heating it up to 500°C	54
4.9	Blank Heating Arrangement with Temperature Measurement	55
4.10	Load cell of the Data Acquisition	57
4.11	Pressure Transducer to measure Blank holding Pressure	58
4.12	Encoder for Punch movement data acquisition	59
4.13	Interface Unit of Data Acquisition system	60

4.14	A 5 Ton Electronically Controlled UTM with furnace	62
4.15	Scanning Electron Microscope	63
4.16	Metallurgical Microscope with image capturing device	64
4.17	Micro Hardness Tester	65
4.18	Pointed Anvil Micrometer	66
4.19	Specimen Drawing for Tensile test (DMRL Practice)	68
4.20	Specimen prepared according to Drawing for Tensile test	69
5.1	Ultimate tensile strength Vs temperature at different orientations	71
5.2	Yield strength Vs temperature at different orientations	72
5.3	Strength coefficient 'K' Vs temperature at different orientations	72
5.4	Work hardening Exponent 'n' Vs temperature at different orientations	73
5.5	Percentage Elongation' Vs temperature at different orientations	73
5.6	Serrations due to DSA explaining Blue Brittle region	75

5.7	SEM images taken for fractures surface of UTM specimen at room temperature (25°C).	78
5.8	SEM images taken for fractures surface of UTM specimen in dynamic strain regime (400°C).	79
5.9	SEM images taken for fractures surface of UTM specimen in plastic region (700°C).	80
6.1	Punch load Vs displacement diagram from the simulation at 2 different punch speeds	88
6.2	A comparison of punch load Vs displacement diagram from the simulation at different coefficient of friction and from experiments at room temperature	89
6.3	A comparison of punch load Vs displacement diagram from the simulation at different coefficient of friction and from experiments at 200° C	90
7.1	Punch load Vs Displacement at 25 % reduction and 200°c	104
7.2	Punch load Vs Displacement at 25 % reduction and 400°c	105
7.3	Punch load Vs Displacement at 25% reduction and 600°c	106
8.1	Micro structures of cup drawn at 40% wall reduction and at 200°C	113
8.2	Micro structures of cup drawn at 25% wall reduction and at 200°C	114
8.3	Micro structures of cup drawn at 10% wall reduction and at 200°C	115

8.4	Micro structures of cup drawn at 25% wall reduction and at 400°C	116
8.5	Micro structures of cup drawn at 25% wall reduction and at 600°C	117
8.6	Variation of Hardness at 200°C for different reductions of wall thickness	118
8.7	Variation of Hardness at 25% wall reduction and for different temperatures	119
9.1	Cups at 40% reduction at 600°C	122
9.2	Fracture at 40% reduction	123
9.3	Cups with 25% reduction and at 200°C	123
9.4	Cups with 25% reduction and at 400°C	124
9.5	Cups with 25% reduction and at 600°C	124
9.6	Cups with 10% reduction and at 200°C	125
9.7	Cups with 10% reduction and at 400°C	125
9.8	Cups with 10% reduction and at 600°C	126
9.9	Punch load Vs displacement graph from the data acquisition system at different blank temperature of 60 mm diameter blank with 25% reduction in thickness	127

9.10	Punch load Vs displacement graph from the data acquisition system at different blank diameters with 40% reduction in thickness and at 600°C blank temperature	128
9.11	Punch load Vs displacement graph from the data acquisition system at different blank temperatures with 60 mm blank diameters and 10% reduction in thickness	129
9.12	Punch load Vs displacement graph from the data acquisition system at different blank temperatures with 62 mm blank diameters and 10% reduction in thickness	130
9.13	Punch load Vs displacement graph from the data acquisition system at different blank temperatures with 65 mm blank diameters and 10% reduction in thickness	131
9.14	Punch load Vs displacement graph from the data acquisition system at different blank diameters 25% reduction in thickness and 400°C blank temperature	132
9.15	Punch load Vs displacement graph from the data acquisition system at different %age reduction in sheet thickness at 600°C blank temperature and 60 mm blank diameter	133
9.16	Thickness of cup Vs distance from the cup centre for different initial blank diameter for 40%	134
9.17	Thickness of cup Vs distance from the cup centre for different initial blank diameter for 25% reduction and at 200°C temperature.	134

9.18	Thickness of cup Vs distance from the cup centre for different initial blank diameter for 25% reduction and at 400°C	135
9.19	Thickness of cup Vs distance from the cup centre for different initial blank diameter for 25% reduction and at 600°C temperature.	136
9.20	Thickness of cup Vs distance from the cup centre for different initial blank temperatures for 25% reduction and for 60 mm blank	137
9.21	Thickness of cup Vs distance from the cup centre for different initial blank diameter for 10% reduction and at 200°C temperature.	138
9.22	Thickness of cup Vs distance from the cup centre for different initial blank diameter for 10% reduction and at 400°C temperature.	138
9.23	Thickness of cup Vs distance from the cup centre for different initial blank diameter for 10% reduction and at 600°C temperature.	139
9.24	Thickness of cup Vs distance from the cup centre for different initial blank temperatures for 10% reduction and for 60 mm blank diameter.	139
9.25	Thickness of cup Vs distance from the cup centre for different %age of deformation for 60 mm initial blank diameter and at 200°C	140
9.26	Thickness of cup Vs distance from the cup centre for different %age of deformation for 60 mm initial blank diameter and at 400°C.	141

9.27	Thickness of cup Vs distance from the cup centre for different %age of deformation for 60 mm initial blank diameter and at 600°C.	141
------	---	-----